



**BRAND
FIRE
PRODUCTS™**

SUBMITTAL SHEET FOR DRY CHEMICAL FIRE EXTINGUISHERS

Oval Fire Extinguisher Features:

- Always complies with protruding object guidelines as listed in ADA, IFC, ANSI A117.1, AODA, and ISO 21542
- Stainless steel pull pin
- Stainless steel handles, bracket and button hook
- Tempered aluminum valve
- Corrosion resistant, tempered aluminum vessel
- Tempered aluminum nozzle
- Heavy duty aluminum siphon tube
- The Oval button hook mounting system reduces the chance of the fire extinguisher falling from its hook.
- Durable powder coat finish
- Serviced same as others, per NFPA 10 requirements
- Labeled "Meets DOT Requirements"
- Labeled per UN1044 requirements
- Most parts are interchangeable
- Made in the USA from 85%+ domestic materials

Please visit the website for:

Health Product Declarations (HPD's) and Safety Data Sheets (SDS).

BIM files including Revit, SketchUp, and AutoCAD.

U.S. Patent Nos. 9,364,696, D760,443, D760,444 and D777,566.



Project: _____

Specification Section: _____

Model No.: _____ Quantity: _____

Model No.: _____ Quantity: _____

Model No.: _____ Quantity: _____

Distributor: _____

Contractor: _____

Architect: _____

Approved by: _____

Date: _____



10JABC



10HABC



10HPKP



Button Hook

AGENT TYPE	ABC DRY CHEMICAL		PURPLE K DRY CHEMICAL
MODEL NUMBER	10JABC	10HABC	10HPKP
UL & ULC RATING	4A:80B:C	4A:80B:C	80B:C
CAPACITY	10 LB (4.6 kg)	10 LB (4.6 kg)	10 LB (4.6 kg)
WEIGHT	24 LB (11.1 kg)	22 LB (10.1 kg)	22 LB (10.1 kg)
HEIGHT	22" (56 cm)	23" (58 cm)	23" (58 cm)
WIDTH OF VESSEL	10" (26 cm)	8" (21 cm)	8" (21 cm)
WIDTH OVERALL	11" (28 cm)	9" (23 cm)	9" (23 cm)
DEPTH	3" (8 cm)	3.5" (9 cm)	3.5" (9 cm)
BEST SUITED FOR	OVAL COMPATIBLE CABINETS	SURFACE MOUNTING	SURFACE MOUNTING
RANGE (INITIAL)	10-15 FT (3-4.5 m)		10-15 FT (3-4.5 m)
DISCHARGE TIME	22 SEC		22 SEC
TEMPERATURE RANGE	-40°F to 120°F (-40°C to 49°C)		-40°F to 120°F (-40°C to 49°C)
MEETS DOT REQUIREMENTS	YES		YES
COMPLIES WITH NFPA 10 STANDARD	YES		YES
MEETS ANSI/UL-299 & ANSI/UL-711	YES		YES
MEETS CAN/ULC-S504 CAN/ULC-S508	YES		YES
OVAL BUTTON HOOK INCLUDED	YES		YES
WARRANTY (FROM DATE MANUFACTURED)	6 YEARS		6 YEARS