



**BRAND
FIRE
PRODUCTS™**

SUBMITTAL SHEET FOR MRI SAFE DRY CHEMICAL FIRE EXTINGUISHERS

Oval Fire Extinguisher Features:

- Always complies with protruding object rules required by ADA, CMS, NFPA-101 LSC, IFC, ANSI A117.1, and AODA
- Durable powder coat finish
- Serviced same as others, per NFPA 10 requirements
- Extinguisher and button hook are non-magnetic
- Independently tested for use in MRI facilities
- Certified MR Conditional to 3 TESLA
- MRI test report available upon request
- The Oval button hook mounting system reduces the chance of the fire extinguisher falling from its hook.
- Stainless steel pull pin
- Stainless steel handles, bracket and button hook
- Tempered aluminum valve and nozzle
- Corrosion resistant, tempered aluminum vessel
- Heavy duty aluminum siphon tube
- Made in the USA from 85%+ domestic materials

Please visit the website for:

Health Product Declarations (HPD's) and Safety Data Sheets (SDS).

BIM files including Revit, SketchUp, and AutoCAD.

U.S. Patent Nos. 9,364,696, D760,443, D760,444 and D777,566.



Project: _____

Specification Section: _____

Model No.: _____ Quantity: _____

Model No.: _____ Quantity: _____

Model No.: _____ Quantity: _____

Distributor: _____

Contractor: _____

Architect: _____

Approved by: _____


Date: _____



10JABC



10HABC



Button Hook

AGENT TYPE	ABC DRY CHEMICAL	
MODEL NUMBER	10JABC-MR	10HABC-MR
UL & ULC RATING	4A:80B:C	4A:80B:C
CAPACITY	10 LB (4.6 kg)	10 LB (4.6 kg)
WEIGHT	24 LB (11.1 kg)	22 LB (10.1 kg)
HEIGHT	22" (56 cm)	23" (58 cm)
WIDTH OF VESSEL	10" (26 cm)	8" (21 cm)
WIDTH OVERALL	11" (28 cm)	9" (23 cm)
DEPTH	3" (8 cm)	3.5" (9 cm)
BEST SUITED FOR	OVAL COMPATIBLE CABINETS	SURFACE MOUNTING
RANGE (INITIAL)	10-15 FT (3-4.5 m)	
DISCHARGE TIME	22 SEC	
TEMPERATURE RANGE	-40°F to 120°F (-40°C to 49°C)	
MEETS DOT REQUIREMENTS	YES	
COMPLIES WITH NFPA 10 STANDARD	YES	
MEETS ANSI/UL-299 & ANSI/UL-711	YES	
MEETS CAN/ULC-S504 CAN/ULC-S508	YES	
OVAL BUTTON HOOK INCLUDED	YES	
WARRANTY (FROM DATE MANUFACTURED)	6 YEARS	