



**BRAND  
FIRE  
PRODUCTS™**

# SUBMITTAL SHEET FOR DRY CHEMICAL FIRE EXTINGUISHERS

**Oval Fire Extinguisher Features:**

- Always complies with protruding object rules required by ADA, CMS, NFPA-101 LSC, IFC, ANSI A117.1, and AODA
- The Oval button hook mounting system reduces the chance of the fire extinguisher falling from its hook.
- Stainless steel pull pin
- Durable powder coat finish
- Stainless steel handles, bracket and button hook
- Serviced same as others, per NFPA 10 requirements
- Tempered aluminum valve and nozzle
- Labeled "Meets DOT Requirements"
- Corrosion resistant, tempered aluminum vessel
- Labeled per UN1044 requirements
- Heavy duty aluminum siphon tube
- Most parts are interchangeable
- MRI safe option available for ABC models
- Made in the USA from 85%+ domestic materials

Project: \_\_\_\_\_

Specification Section: \_\_\_\_\_

Model No.: \_\_\_\_\_ Quantity: \_\_\_\_\_

Model No.: \_\_\_\_\_ Quantity: \_\_\_\_\_

Model No.: \_\_\_\_\_ Quantity: \_\_\_\_\_

Distributor: \_\_\_\_\_

Contractor: \_\_\_\_\_

Architect: \_\_\_\_\_

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_



Please visit the website for:

Health Product Declarations (HPD's) and Safety Data Sheets (SDS).

BIM files including Revit, SketchUp, and AutoCAD.

U.S. Patent Nos. 9,364,696, D760,443, D760,444 and D777,566.



AGENT TYPE	ABC DRY CHEMICAL		PURPLE K DRY CHEMICAL
MODEL NUMBER	10JABC	10HABC	10HPKP
UL & ULC RATING	4A:80B:C	4A:80B:C	80B:C
CAPACITY	10 LB (4.6 kg)	10 LB (4.6 kg)	10 LB (4.6 kg)
WEIGHT	24 LB (11.1 kg)	22 LB (10.1 kg)	22 LB (10.1 kg)
HEIGHT	22" (56 cm)	23" (58 cm)	23" (58 cm)
WIDTH OF VESSEL	10" (26 cm)	8" (21 cm)	8" (21 cm)
WIDTH OVERALL	11" (28 cm)	9" (23 cm)	9" (23 cm)
DEPTH	3" (8 cm)	3.5" (9 cm)	3.5" (9 cm)
BEST SUITED FOR	OVAL COMPATIBLE CABINETS	SURFACE MOUNTING	SURFACE MOUNTING
RANGE (INITIAL)	10-15 FT (3-4.5 m)		10-15 FT (3-4.5 m)
DISCHARGE TIME	22 SEC		22 SEC
TEMPERATURE RANGE	-40°F to 120°F (-40°C to 49°C)		-40°F to 120°F (-40°C to 49°C)
MEETS DOT REQUIREMENTS	YES		YES
COMPLIES WITH NFPA 10 STANDARD	YES		YES
MEETS ANSI/UL-299 & ANSI/UL-711	YES		YES
MEETS CAN/ULC-S504 CAN/ULC-S508	YES		YES
OVAL BUTTON HOOK INCLUDED	YES		YES
WARRANTY (FROM DATE MANUFACTURED)	6 YEARS		6 YEARS