



BRAND
FIRE
PRODUCTS™

Introducing the ONLY fire extinguisher built for NFPA-101 Life Safety Code & ADA compliance.

The Problem: Healthcare, hospital, ambulatory, long-term care, and senior living facilities must now comply with the 2012 edition of NFPA-101. Noncontinuous projections in corridors located below 38" are now limited to 4-1/2". Projections above 38" are limited to no more than 4" per ADA and CMS. Most fire extinguishers, if surface mounted, do not comply with the new requirements.

The Solution: Oval Brand Fire Products is proud to introduce the first and only fire extinguisher built for both NFPA-101 and ADA compliance, as required by CMS. By flattening the tank into a low-profile shape, Oval has created an extinguisher that projects less than 4" from the wall. The fire extinguisher can be mounted at the required locations and still remain compliant.

Due to the recently issued requirements by the Centers for Medicare & Medicaid Services (CMS), Oval Brand's low profile fire extinguishers are the only fire extinguishers which may be surface mounted in the corridors of healthcare facilities while maintaining compliance with the NFPA-101 Life Safety Code (2012 edition) and the ADA. All other brands' 5 lb and 10 lb fire extinguishers protrude more than 4-1/2" when surface mounted, however Oval's UL listed fire extinguishers project less than 4" and are always compliant.

US Patents: 9,364,696; D760,443; D760,444; D777,566

For more information and a free demonstration, contact your local fire equipment distributor, industrial supply distributor or visit ovalfireproducts.com.



*Innovating Unparalleled
Fire Protection Products*



**BRAND
FIRE
PRODUCTS™**

Oval fire extinguishers may be either mounted on a wall or column or installed in a fire extinguisher cabinet. In either case, the installation facilitates compliance with ADA, NFPA-101, and CMS requirements.

Surface Mounting Surface mounted fire extinguishers are furnished with a patented swivel mounting hook for exposed mounting on a wall or column. The fire extinguisher projects 3 1/2" from the wall surface. The unique swivel hook assures that, if the fire extinguisher is accidentally bumped or hit, it will swivel out of the way rather than be damaged or dislodged from the wall or column.

Model	Description	Rating
10HABC	10 lb ABC Dry Chemical	4-A:80-B:C
10HABC-MR	10 lb ABC Dry Chemical MRI Safe, Rated to 3-Tesla	4-A:80-B:C
10HPKP	10 lb Purple K Dry Chemical	80-B:C



Cabinet Mounting Fire extinguishers may also be installed in a recessed cabinet (supplied separately). Fire extinguishers for cabinet mounting are 3" deep.

Oval recessed cabinets fit into 2 1/2" and 3 5/8" stud walls and 6" masonry walls. Oval fire-rated cabinets fit into 3 5/8" stud walls. With Oval fire extinguishers and cabinets, it is no longer necessary to build an extra deep wall just for the fire extinguisher.

Model	Description	Rating
10JABC	10 lb ABC Dry Chemical	4-A:80-B:C
10JABC-MR	10 lb ABC Dry Chemical MRI Safe, Rated to 3-Tesla	4-A:80-B:C



US Patents: 9,364,696; D760,443; D760,444; D777,566

Note: Oval Brand fire extinguishers are designed to facilitate compliance with ADA and other limits for protrusion of objects mounted at aisles, walkways and other circulation paths. Like all fire extinguishers, Oval products require grasping, more than 5 lbs force to actuate and two hands to operate.

*Innovating Unparalleled
Fire Protection Products*

